

DMG MORI CMX 50U



TECHNICAL DATA

<i>Model</i>	DMG MORI CMX 50U
<i>Type machine</i>	Vertical Milling 5 axis
<i>Tool magazine</i>	30pos
<i>Max Speed</i>	12000 U/min
<i>Internal coolant supply</i>	40 bar
<i>Control</i>	SIEMENS 840D

WORK AREA

X - axis	500 (mm)
Y - axis	450 (mm)
Z - axis	400 (mm)
B - axis	-5° / +110°
C - axis	0 / 360°

HARDINGE BRIDGEPORT XR1600



TECHNICAL DATA

<i>Model</i>	HARDINGE BRIDGEPORT XR1600
<i>Type machine</i>	Vertical Milling 3 axis
<i>Tool magazine</i>	30pos
<i>Max Speed</i>	10000 U/min
<i>Internal coolant supply</i>	30 bar
<i>Control</i>	FANUC 18i-MB

WORK AREA

X - axis	1600 (mm)
Y - axis	700 (mm)
Z - axis	700 (mm)

HARDINGE BRIDGEPORT VMC600P



TECHNICAL DATA

<i>Model</i>	HARDINGE BRIDGEPORT XR1600
<i>Type machine</i>	Vertical Milling 3 axis
<i>Tool magazine</i>	20pos
<i>Max Speed</i>	8000 U/min
<i>Internal coolant supply</i>	20 bar
<i>Control</i>	FANUC 0i-MC

WORK AREA

X - axis	600 (mm)
Y - axis	400 (mm)
Z - axis	500 (mm)

2 x SUPERMAX 72A



TECHNICAL DATA

Model	SUPERMAX 72A
Type machine	Vertical Milling 3 axis
Tool magazine	24pos
Max Speed	6000 U/min
Control	FANUC 0-M

WORK AREA

X - axis	860 (mm)
Y - axis	440 (mm)
Z - axis	650 (mm)

FAMUP MCX600



TECHNICAL DATA

<i>Model</i>	FAMUP MCX600
<i>Type machine</i>	Vertical Milling 4 axis
<i>Tool magazine</i>	18pos
<i>Max Speed</i>	4000 U/min
<i>Control</i>	FANUC 0-M

WORK AREA

X - axis	450 (mm)
Y - axis	350 (mm)
Z - axis	500 (mm)
B - axis	0° / 360°